



AiP74AUP1G08

Low Power Single 2-input And Gate

Product Specification

Specification Revision History:

Version	Date	Description
2019-12-A1	2019-12	New
2023-04-B1	2023-04	Update the template



Contents

1、General Description.....	3
2、Block Diagram And Pin Description	4
2.1、Block Diagram	4
2.2、Pin Configurations.....	4
2.3、Pin Description.....	4
2.4、Function Table.....	5
3、Electrical Parameter	5
3.1、Absolute Maximum Ratings.....	5
3.2、Recommended Operating Conditions	5
3.3、Electrical Characteristics.....	6
3.3.1、DC Characteristics 1	6
3.3.2、DC Characteristics 2	7
3.3.3、DC Characteristics 3.....	8
3.3.4、AC Characteristics 1	9
3.3.5、AC Characteristics 2.....	10
3.3.6、AC Characteristics 3.....	11
4、Testing Circuit	12
4.1、AC Testing Circuit	12
4.2、AC Testing Waveforms.....	12
4.3、Measurement Points	12
4.4、Test Data	12
5、Package Information	13
5.1、SOT23-5.....	13
5.2、SOT353	14
6、Statements And Notes	15
6.1、The name and content of Hazardous substances or Elements in the product.....	15
6.2、Notes	15



1、General Description

The AiP74AUP1G08 provides the single 2-input AND function.

This device ensures a very low static and dynamic power consumption across the entire V_{CC} range from 0.8V to 3.6V.

This device is fully specified for partial Power-down applications using I_{OFF} . The I_{OFF} circuitry disables the output, preventing the damaging backflow current through the device when it is powered down.

Features:

- Wide supply voltage range from 0.8V to 3.6V
- Low static power consumption; $I_{CC}=1\mu A$ (maximum)
- Inputs accept voltages up to 3.6V
- I_{OFF} circuitry provides partial Power-down mode operation
- Specified from $-40^{\circ}C$ to $+125^{\circ}C$
- Packaging information: SOT23-5/SOT353

Ordering Information:

Reel packing specifications:

Part number	Packaging form	Marking code	Reel quantity	Boxed reel quantity	Notes
AiP74AUP1G08GB235.TR	SOT23-5	CTXX	3000 PCS/reel	30000 PCS/box	Dimensions of plastic enclosure: 2.9mm×1.6mm Pin spacing: 0.95mm
AiP74AUP1G08GC353.TR	SOT353	CTXX	3000 PCS/reel	30000 PCS/box	Dimensions of plastic enclosure: 2.1mm×1.3mm Pin spacing: 0.65mm

Note 1: “XX” refers to variable content, meaning year and package batch serial number.

Note 2: If the physical information is inconsistent with the ordering information, please refer to the actual product.



2、Block Diagram And Pin Description

2.1、Block Diagram




Figure 1. Logic symbol



Figure 2. IEC logic symbol





Figure 3. Logic diagram

2.2、Pin Configurations



2.3、Pin Description

Pin No.	Pin Name	Description
1	B	data input
2	A	data input
3	GND	ground(0V)
4	Y	data output
5	V _{CC}	supply voltage



2.4、Function Table

Input		Output
A	B	Y
L	L	L
L	H	L
H	L	L
H	H	H

Note: H=HIGH voltage level; L=LOW voltage level.

3、Electrical Parameter

3.1、Absolute Maximum Ratings

($T_{amb}=25^{\circ}\text{C}$, voltages are referenced to GND (ground=0V), unless otherwise specified)

Characteristic	Symbol	Conditions	Min.	Max.	Unit
supply voltage	V_{CC}	-	-0.5	+4.6	V
input clamping current	I_{IK}	$V_I < 0V$	-50	-	mA
input voltage	V_I	- ^[1]	-0.5	+4.6	V
output clamping current	I_{OK}	$V_O < 0V$	-	± 20	mA
output voltage	V_O	Active mode and Power-down mode ^[1]	-0.5	+4.6	V
output current	I_O	$V_O = 0V$ to V_{CC}	-	± 20	mA
supply current	I_{CC}	-	-	+50	mA
ground current	I_{GND}	-	-50	-	mA
storage temperature	T_{stg}	-	-65	+150	$^{\circ}\text{C}$
total power dissipation	P_{tot}	-	-	250	mW
soldering temperature	T_L	-	260		$^{\circ}\text{C}$

Note:

[1] The minimum input and output voltage ratings may be exceeded if the input and output current ratings are observed.

3.2、Recommended Operating Conditions

Parameter	Symbol	Conditions	Min.	Typ.	Max.	Unit
supply voltage	V_{CC}	-	0.8	-	3.6	V
input voltage	V_I	-	0	-	3.6	V
output voltage	V_O	Active mode	0	-	V_{CC}	V
		Power-down mode; $V_{CC}=0V$	0	-	3.6	V
ambient temperature	T_{amb}	-	-40	-	+125	$^{\circ}\text{C}$
input transition rise and fall rate	$\Delta t/\Delta V$	$V_{CC}=0.8V$ to $3.6V$	0	-	200	ns/V



3.3、Electrical Characteristics

3.3.1、DC Characteristics 1

($T_{amb}=25^{\circ}\text{C}$, voltages are referenced to GND (ground=0V), unless otherwise specified)

Parameter	Symbol	Conditions	Min.	Typ.	Max.	Unit
HIGH-level input voltage	V_{IH}	$V_{CC}=0.8\text{V}$	$0.70 \times V_{CC}$	-	-	V
		$V_{CC}=0.9\text{V to } 1.95\text{V}$	$0.65 \times V_{CC}$	-	-	V
		$V_{CC}=2.3\text{V to } 2.7\text{V}$	1.6	-	-	V
		$V_{CC}=3.0\text{V to } 3.6\text{V}$	2.0	-	-	V
LOW-level input voltage	V_{IL}	$V_{CC}=0.8\text{V}$	-	-	$0.30 \times V_{CC}$	V
		$V_{CC}=0.9\text{V to } 1.95\text{V}$	-	-	$0.35 \times V_{CC}$	V
		$V_{CC}=2.3\text{V to } 2.7\text{V}$	-	-	0.7	V
		$V_{CC}=3.0\text{V to } 3.6\text{V}$	-	-	0.9	V
HIGH-level output voltage	V_{OH}	$V_I = V_{IH} \text{ or } V_{IL}$	$I_O = -20\mu\text{A}; V_{CC}=0.8\text{V to } 3.6\text{V}$	$V_{CC}-0.1$	-	V
			$I_O = -1.1\text{mA}; V_{CC}=1.1\text{V}$	$0.75 \times V_{CC}$	-	V
			$I_O = -1.7\text{mA}; V_{CC}=1.4\text{V}$	1.11	-	V
			$I_O = -1.9\text{mA}; V_{CC}=1.65\text{V}$	1.32	-	V
			$I_O = -2.3\text{mA}; V_{CC}=2.3\text{V}$	2.05	-	V
			$I_O = -3.1\text{mA}; V_{CC}=2.3\text{V}$	1.9	-	V
			$I_O = -2.7\text{mA}; V_{CC}=3.0\text{V}$	2.72	-	V
			$I_O = -4.0\text{mA}; V_{CC}=3.0\text{V}$	2.6	-	V
LOW-level output voltage	V_{OL}	$V_I = V_{IH} \text{ or } V_{IL}$	$I_O = 20\mu\text{A}; V_{CC}=0.8\text{V to } 3.6\text{V}$	-	0.1	V
			$I_O = 1.1\text{mA}; V_{CC}=1.1\text{V}$	-	$0.3 \times V_{CC}$	V
			$I_O = 1.7\text{mA}; V_{CC}=1.4\text{V}$	-	0.31	V
			$I_O = 1.9\text{mA}; V_{CC}=1.65\text{V}$	-	0.31	V
			$I_O = 2.3\text{mA}; V_{CC}=2.3\text{V}$	-	0.31	V
			$I_O = 3.1\text{mA}; V_{CC}=2.3\text{V}$	-	0.44	V
			$I_O = 2.7\text{mA}; V_{CC}=3.0\text{V}$	-	0.31	V
			$I_O = 4.0\text{mA}; V_{CC}=3.0\text{V}$	-	0.44	V
input leakage current	I_I	$V_I = \text{GND to } 3.6\text{V}; V_{CC}=0\text{V to } 3.6\text{V}$	-	-	± 1.0	μA
power-off leakage current	I_{OFF}	$V_I \text{ or } V_O = 0\text{V to } 3.6\text{V}; V_{CC}=0\text{V}$	-	-	± 1.0	μA
additional power-off leakage current	ΔI_{OFF}	$V_I \text{ or } V_O = 0\text{V to } 3.6\text{V}; V_{CC}=0\text{V to } 0.2\text{V}$	-	-	± 1.0	μA
supply current	I_{CC}	$V_I = \text{GND or } V_{CC}; I_O = 0\text{A}; V_{CC}=0.8\text{V to } 3.6\text{V}$	-	-	1.0	μA
additional supply current	ΔI_{CC}	$V_I = V_{CC}-0.6\text{V}; I_O = 0\text{A}; V_{CC}=3.3\text{V}^{[1]}$	-	-	40	μA
input capacitance	C_I	$V_{CC}=0\text{V to } 3.6\text{V}; V_I = \text{GND or } V_{CC}$	-	0.8	-	pF
output capacitance	C_O	$V_O = \text{GND}; V_{CC}=0\text{V}$	-	1.7	-	pF



Note:

[1] One input at $V_{CC}-0.6V$, other input at V_{CC} or GND.

3.3.2、DC Characteristics 2

(T_{amb}=-40°C to +85°C, voltages are referenced to GND (ground=0V), unless otherwise specified)

Parameter	Symbol	Conditions		Min.	Typ.	Max.	Unit
HIGH-level input voltage	V _{IH}	V _{CC} =0.8V		0.70×V _{CC}	-	-	V
		V _{CC} =0.9V to 1.95V		0.65×V _{CC}	-	-	V
		V _{CC} =2.3V to 2.7V		1.6	-	-	V
		V _{CC} =3.0V to 3.6V		2.0	-	-	V
LOW-level input voltage	V _{IL}	V _{CC} =0.8V		-	-	0.30×V _{CC}	V
		V _{CC} =0.9V to 1.95V		-	-	0.35×V _{CC}	V
		V _{CC} =2.3V to 2.7V		-	-	0.7	V
		V _{CC} =3.0V to 3.6V		-	-	0.9	V
HIGH-level output voltage	V _{OH}	V _I =V _{IH} or V _{IL}	I _O =-20uA; V _{CC} =0.8V to 3.6V	V _{CC} -0.1	-	-	V
			I _O =-1.1mA; V _{CC} =1.1V	0.7×V _{CC}	-	-	V
			I _O =-1.7mA; V _{CC} =1.4V	1.03	-	-	V
			I _O =-1.9mA; V _{CC} =1.65V	1.30	-	-	V
			I _O =-2.3mA; V _{CC} =2.3V	1.97	-	-	V
			I _O =-3.1mA; V _{CC} =2.3V	1.85	-	-	V
			I _O =-2.7mA; V _{CC} =3.0V	2.67	-	-	V
			I _O =-4.0mA; V _{CC} =3.0V	2.55	-	-	V
LOW-level output voltage	V _{OL}	V _I =V _{IH} or V _{IL}	I _O =20uA; V _{CC} =0.8V to 3.6V	-	-	0.1	V
			I _O =1.1mA; V _{CC} =1.1V	-	-	0.3×V _{CC}	V
			I _O =1.7mA; V _{CC} =1.4V	-	-	0.37	V
			I _O =1.9mA; V _{CC} =1.65V	-	-	0.35	V
			I _O =2.3mA; V _{CC} =2.3V	-	-	0.33	V
			I _O =3.1mA; V _{CC} =2.3V	-	-	0.45	V
			I _O =2.7mA; V _{CC} =3.0V	-	-	0.33	V
			I _O =4.0mA; V _{CC} =3.0V	-	-	0.45	V
input leakage current	I _I	V _I =GND to 3.6V; V _{CC} =0V to 3.6V		-	-	±1.0	uA
power-off leakage current	I _{OFF}	V _I or V _O =0V to 3.6V; V _{CC} =0V		-	-	±1.0	uA
additional power-off leakage current	ΔI _{OFF}	V _I or V _O =0V to 3.6V; V _{CC} =0V to 0.2V		-	-	±1.0	uA
supply current	I _{CC}	V _I =GND or V _{CC} ; I _O =0A; V _{CC} =0.8V to 3.6V		-	-	1.0	uA
additional supply current	ΔI _{CC}	V _I =V _{CC} -0.6V; I _O =0A; V _{CC} =3.3V ^[1]		-	-	50	uA

Note:

[1] One input at $V_{CC}-0.6V$, other input at V_{CC} or GND.

**3.3.3、DC Characteristics 3**(T_{amb}=-40°C to +125°C, voltages are referenced to GND (ground=0V), unless otherwise specified)

Parameter	Symbol	Conditions		Min.	Typ.	Max.	Unit
HIGH-level input voltage	V _{IH}	V _{CC} =0.8V		0.75×V _{CC}	-	-	V
		V _{CC} =0.9V to 1.95V		0.70×V _{CC}	-	-	V
		V _{CC} =2.3V to 2.7V		1.6	-	-	V
		V _{CC} =3.0V to 3.6V		2.0	-	-	V
LOW-level input voltage	V _{IL}	V _{CC} =0.8V		-	-	0.25×V _{CC}	V
		V _{CC} =0.9V to 1.95V		-	-	0.30×V _{CC}	V
		V _{CC} =2.3V to 2.7V		-	-	0.7	V
		V _{CC} =3.0V to 3.6V		-	-	0.9	V
HIGH-level output voltage	V _{OH}	V _I =V _{IH} or V _{IL}	I _O =-20uA; V _{CC} =0.8V to 3.6V	V _{CC} -0.11	-	-	V
			I _O =-1.1mA; V _{CC} =1.1V	0.6×V _{CC}	-	-	V
			I _O =-1.7mA; V _{CC} =1.4V	0.93	-	-	V
			I _O =-1.9mA; V _{CC} =1.65V	1.17	-	-	V
			I _O =-2.3mA; V _{CC} =2.3V	1.77	-	-	V
			I _O =-3.1mA; V _{CC} =2.3V	1.67	-	-	V
			I _O =-2.7mA; V _{CC} =3.0V	2.40	-	-	V
			I _O =-4.0mA; V _{CC} =3.0V	2.30	-	-	V
LOW-level output voltage	V _{OL}	V _I =V _{IH} or V _{IL}	I _O =20uA; V _{CC} =0.8V to 3.6V	-	-	0.11	V
			I _O =1.1mA; V _{CC} =1.1V	-	-	0.33×V _{CC}	V
			I _O =1.7mA; V _{CC} =1.4V	-	-	0.41	V
			I _O =1.9mA; V _{CC} =1.65V	-	-	0.39	V
			I _O =2.3mA; V _{CC} =2.3V	-	-	0.36	V
			I _O =3.1mA; V _{CC} =2.3V	-	-	0.50	V
			I _O =2.7mA; V _{CC} =3.0V	-	-	0.36	V
			I _O =4.0mA; V _{CC} =3.0V	-	-	0.50	V
input leakage current	I _I	V _I =GND to 3.6V; V _{CC} =0V to 3.6V		-	-	±1.0	uA
power-off leakage current	I _{OFF}	V _I or V _O =0V to 3.6V; V _{CC} =0V		-	-	±1.0	uA
additional power-off leakage current	ΔI _{OFF}	V _I or V _O =0V to 3.6V; V _{CC} =0V to 0.2V		-	-	±1.0	uA
supply current	I _{CC}	V _I =GND or V _{CC} ; I _O =0A; V _{CC} =0.8V to 3.6V		-	-	1.4	uA
additional supply current	ΔI _{CC}	V _I =V _{CC} -0.6V; I _O =0A; V _{CC} =3.3V ^[1]		-	-	75	uA

Note:

[1] One input at V_{CC}-0.6V, other input at V_{CC} or GND.



3.3.4、AC Characteristics 1

($T_{amb}=25^{\circ}\text{C}$, voltages are referenced to GND (ground=0V), unless otherwise specified)

Parameter	Symbol	Conditions		Min.	Typ. ^[1]	Max.	Unit
propagation delay	t _{pd}	A, B to Y; see Figure 5 ^[2]	C _L =5pF				
			V _{CC} =0.8V	-	17.0	-	ns
			V _{CC} =1.1V to 1.3V	2.6	5.1	10.8	ns
			V _{CC} =1.4V to 1.6V	1.6	3.7	6.5	ns
			V _{CC} =1.65V to 1.95V	1.3	3.0	5.2	ns
			V _{CC} =2.3V to 2.7V	1.1	2.4	4.0	ns
			V _{CC} =3.0V to 3.6V	1.0	2.2	3.5	ns
			C _L =10pF				
			V _{CC} =0.8V	-	20.6	-	ns
			V _{CC} =1.1V to 1.3V	2.4	6.0	12.5	ns
			V _{CC} =1.4V to 1.6V	2.0	4.3	7.6	ns
			V _{CC} =1.65V to 1.95V	1.7	3.6	6.1	ns
			V _{CC} =2.3V to 2.7V	1.4	2.9	4.8	ns
			V _{CC} =3.0V to 3.6V	1.3	2.7	4.2	ns
			C _L =15pF				
			V _{CC} =0.8V	-	24.1	-	ns
			V _{CC} =1.1V to 1.3V	3.4	6.8	14.2	ns
			V _{CC} =1.4V to 1.6V	2.3	4.9	8.6	ns
			V _{CC} =1.65V to 1.95V	1.9	4.0	6.9	ns
			V _{CC} =2.3V to 2.7V	1.7	3.4	5.5	ns
			V _{CC} =3.0V to 3.6V	1.5	3.1	4.8	ns
			C _L =30pF				
			V _{CC} =0.8V	-	34.4	-	ns
			V _{CC} =1.1V to 1.3V	4.6	9.1	19.4	ns
			V _{CC} =1.4V to 1.6V	3.4	6.4	11.5	ns
			V _{CC} =1.65V to 1.95V	2.6	5.3	9.1	ns
			V _{CC} =2.3V to 2.7V	2.3	4.5	7.2	ns
			V _{CC} =3.0V to 3.6V	2.2	4.2	6.2	ns
power dissipation capacitance	C _{PD}	f=1MHz; V _I =GND to V _{CC} ^[3]	V _{CC} =0.8V	-	2.5	-	pF
			V _{CC} =1.1V to 1.3V	-	2.7	-	pF
			V _{CC} =1.4V to 1.6V	-	2.8	-	pF
			V _{CC} =1.65V to 1.95V	-	2.9	-	pF
			V _{CC} =2.3V to 2.7V	-	3.5	-	pF
			V _{CC} =3.0V to 3.6V	-	4.0	-	pF

Note:

[1] All typical values are measured at nominal V_{CC} .

[2] t_{pd} is the same as t_{PLH} and t_{PHL} .

[3] C_{PD} is used to determine the dynamic power dissipation (P_D in uW).

$P_D=C_{PD} \times V_{CC}^2 \times f_i \times N + \Sigma(C_L \times V_{CC}^2 \times f_o)$ where:

f_i =input frequency in MHz;

f_o =output frequency in MHz;

C_L =output load capacitance in pF;

V_{CC} =supply voltage in V;



N=number of inputs switching;

$\Sigma(C_L \times V_{CC}^2 \times f_o)$ =sum of the outputs.

3.3.5、AC Characteristics 2

($T_{amb}=-40^{\circ}\text{C}$ to $+85^{\circ}\text{C}$, voltages are referenced to GND (ground=0V), unless otherwise specified)

Parameter	Symbol	Conditions	Min.	Typ.	Max.	Unit	
propagation delay	t _{pd}	A, B to Y; see Figure 5 ^[1]	C _L =5pF				
			V _{CC} =1.1V to 1.3V	2.1	-	11.7	ns
			V _{CC} =1.4V to 1.6V	1.5	-	7.5	ns
			V _{CC} =1.65V to 1.95V	1.3	-	6.1	ns
			V _{CC} =2.3V to 2.7V	1.0	-	4.8	ns
			V _{CC} =3.0V to 3.6V	0.9	-	4.3	ns
			C _L =10pF				
			V _{CC} =1.1V to 1.3V	2.2	-	13.6	ns
			V _{CC} =1.4V to 1.6V	1.8	-	8.9	ns
			V _{CC} =1.65V to 1.95V	1.6	-	7.2	ns
			V _{CC} =2.3V to 2.7V	1.3	-	5.7	ns
			V _{CC} =3.0V to 3.6V	1.2	-	4.7	ns
			C _L =15pF				
			V _{CC} =1.1V to 1.3V	3.1	-	15.7	ns
			V _{CC} =1.4V to 1.6V	2.1	-	10.1	ns
			V _{CC} =1.65V to 1.95V	1.8	-	8.2	ns
			V _{CC} =2.3V to 2.7V	1.6	-	6.5	ns
			V _{CC} =3.0V to 3.6V	1.5	-	5.9	ns
			C _L =30pF				
			V _{CC} =1.1V to 1.3V	4.1	-	21.8	ns
			V _{CC} =1.4V to 1.6V	2.9	-	13.6	ns
			V _{CC} =1.65V to 1.95V	2.4	-	10.9	ns
			V _{CC} =2.3V to 2.7V	2.2	-	8.6	ns
			V _{CC} =3.0V to 3.6V	2.1	-	7.5	ns

Note:

[1] t_{pd} is the same as t_{PLH} and t_{PHL} .



3.3.6、AC Characteristics 3

($T_{amb} = -40^{\circ}\text{C}$ to $+125^{\circ}\text{C}$, voltages are referenced to GND (ground=0V), unless otherwise specified)

Parameter	Symbol	Conditions		Min.	Typ.	Max.	Unit
propagation delay	t _{pd}	A, B to Y; see Figure 5 ^[1]	C _L =5pF				
			V _{CC} =1.1V to 1.3V	2.1	-	12.9	ns
			V _{CC} =1.4V to 1.6V	1.5	-	8.3	ns
			V _{CC} =1.65V to 1.95V	1.3	-	6.7	ns
			V _{CC} =2.3V to 2.7V	1.0	-	5.3	ns
			V _{CC} =3.0V to 3.6V	0.9	-	4.8	ns
			C _L =10pF				
			V _{CC} =1.1V to 1.3V	2.2	-	15.0	ns
			V _{CC} =1.4V to 1.6V	1.8	-	9.8	ns
			V _{CC} =1.65V to 1.95V	1.6	-	7.9	ns
			V _{CC} =2.3V to 2.7V	1.3	-	6.3	ns
			V _{CC} =3.0V to 3.6V	1.2	-	5.2	ns
			C _L =15pF				
			V _{CC} =1.1V to 1.3V	3.1	-	17.3	ns
			V _{CC} =1.4V to 1.6V	2.1	-	11.2	ns
			V _{CC} =1.65V to 1.95V	1.8	-	9.0	ns
			V _{CC} =2.3V to 2.7V	1.6	-	7.2	ns
			V _{CC} =3.0V to 3.6V	1.5	-	6.5	ns
			C _L =30pF				
			V _{CC} =1.1V to 1.3V	4.1	-	24.0	ns
			V _{CC} =1.4V to 1.6V	2.9	-	15.0	ns
			V _{CC} =1.65V to 1.95V	2.4	-	12.1	ns
			V _{CC} =2.3V to 2.7V	2.2	-	9.5	ns
			V _{CC} =3.0V to 3.6V	2.1	-	8.3	ns

Note:

[1] t_{pd} is the same as t_{PLH} and t_{PHL} .



4、Testing Circuit

4.1、AC Testing Circuit




Figure 4. Test circuit for measuring switching times

Definitions for test circuit:


R_L =Load resistance.

C_L =Load capacitance including jig and probe capacitance.

R_T =Termination resistance should be equal to the output impedance Z_o of the pulse generator.

V_{EXT} =External voltage for measuring switching times.

4.2、AC Testing Waveforms



Logic levels: V_{OL} and V_{OH} are typical output voltage levels that occur with the output load.

Figure 5. The data input (A or B) to output (Y) propagation delays

4.3、Measurement Points

Supply voltage	Output	Input		
V_{CC}	V_M	V_M	V_I	$t_r=t_f$
0.8V to 3.6V	$0.5 \times V_{CC}$	$0.5 \times V_{CC}$	V_{CC}	$\leq 3.0\text{ns}$

4.4、Test Data

Supply voltage	Load		V_{EXT}		
V_{CC}	C_L	$R_L^{[1]}$	t_{PLH}, t_{PHL}	t_{PZH}, t_{PHZ}	t_{PZL}, t_{PLZ}
0.8V to 3.6V	5pF, 10pF, 15pF and 30pF	5kΩ or 1MΩ	open	GND	$2 \times V_{CC}$


Note:

[1] For measuring enable and disable times $R_L=5\text{k}\Omega$, for measuring propagation delays, setup and hold times and pulse width $R_L=1\text{M}\Omega$.



5、Package Information




5.1、SOT23-5



Symbol	Dimensions (mm)	
	Min.	Max.
A	-	1.26
A1	0.00	0.12
A2	1.00	1.20
b	0.30	0.50
c	0.10	0.20
D	2.82	3.02
E	2.60	3.00
E1	1.50	1.70
e	0.95	
e1	1.80	2.00
L	0.30	0.60
θ	0°	8°



5.2、SOT353



Symbol	Dimensions (mm)	
	Min.	Max.
A	0.90	1.10
A1	0.00	0.10
A2	0.90	1.00
b	0.15	0.35
c	0.11	0.175
D	2.00	2.20
E	1.15	1.35
E1	2.15	2.45
e	0.65	
e1	1.20	1.40
L	0.525	
L1	0.26	0.46
θ	0°	8°



6、Statements And Notes

6.1、The name and content of Hazardous substances or Elements in the product

Part name	Hazardous substances or Elements									
	Lead and lead compounds	Mercury and mercury compounds	Cadmium and cadmium compounds	Hexavalent chromium compounds	Polybrominated biphenyls	Polybrominated biphenyl ethers	Dibutyl phthalate	Butylbenzyl phthalate	Di-2-ethylhexyl phthalate	Diisobutyl phthalate
Lead frame	○	○	○	○	○	○	○	○	○	○
Plastic resin	○	○	○	○	○	○	○	○	○	○
Chip	○	○	○	○	○	○	○	○	○	○
The lead	○	○	○	○	○	○	○	○	○	○
Plastic sheet installed	○	○	○	○	○	○	○	○	○	○
explanation	○: Indicates that the content of hazardous substances or elements in the detection limit of the following the SJ/T11363-2006 standard. ×: Indicates that the content of hazardous substances or elements exceeding the SJ/T11363-2006 Standard limit requirements.									

6.2、Notes

We Recommend you to read this chapter carefully before using this product.

The information in this chapter is provided for reference only and i-Core disclaims any express or implied warranties, including but not limited to applicability, special application or non-infringement of third party rights.

This product is not suitable for critical equipment such as life-saving, life-sustaining or safety equipment. It is also not suitable for applications that may result in personal injury, death, or serious property or environmental damage due to product malfunction or failure. I-Core will not be liable for any damages incurred by the customers at their own risk for such applications.

The customer is responsible for conducting all necessary tests i-Core's application to avoid failure in the application or the application of the customer's third party users. I-Core does not accept any liability.

The Company reserves the right to change or improve the information published in this chapter at any time. The information in this chapter are subject to change without notice. We recommend the customer to consult our sales staff before purchasing.

Please obtain related materials form i-Core's regular channels and we are not responsible for its content if it is provided by sources other than our company.

In case of any conflict between the Chinese and English version, the version is subject to the Chinese one.