



AiP74LV1T32

2-Input Single Supply Translating Or Gate

Product Specification

Specification Revision History:

Version	Date	Description
2024-01-A0	2024-01	New



Contents

1、General Description.....	3
2、Block Diagram And Pin Description	4
2.1、Block Diagram	4
2.2、Pin Configurations.....	4
2.3、Pin Description.....	4
2.4、Function Table.....	5
3.1、Absolute Maximum Ratings.....	5
3.2、Recommended Operating Conditions.....	5
3.3、Electrical Characteristics	6
3.3.1、DC Characteristics 1.....	6
3.3.2、DC Characteristics 2.....	7
3.3.3、DC Characteristics 3.....	8
3.3.4、AC Characteristics 1.....	9
3.3.5、AC Characteristics 2.....	9
3.3.6、AC Characteristics 3.....	10
4、Testing Circuit	10
4.1、AC Testing Circuit	10
4.3、AC Testing Waveforms.....	11
4.4、Measurement Points	11
5、Package Information	12
5.1、SOT23-5	12
5.2、SOT353	13
6、Statements And Notes	14
6.1、The name and content of Hazardous substances or Elements in the product.....	14
6.2、Notes	14



1、General Description

The AiP74LV1T32 is a single, level translating 2-input OR gate. The low threshold inputs support 1.8V input logic at $V_{CC}=3.3V$ and can be used in 1.8V to 3.3V level up translation. In addition, the 5V tolerant input pins enable level down translation (3.3V to 2.5V output at $V_{CC}=2.5V$). The output level is referenced to the supply voltage and supports 1.8V, 2.5V, 3.3V and 5.0V CMOS levels.

Features:

- Supply voltage: 1.8V to 5.0V
- Up translation
 - 1.2V to 1.8V at $V_{CC}=1.8V$
 - 1.5V to 2.5V at $V_{CC}=2.5V$
 - 1.8V to 3.3V at $V_{CC}=3.3V$
 - 3.3V to 5.0V at $V_{CC}=5.0V$
- Down translation
 - 3.3V to 1.8V at $V_{CC}=1.8V$
 - 3.3V to 2.5V at $V_{CC}=2.5V$
 - 5.0V to 3.3V at $V_{CC}=3.3V$
- Inputs accept voltages to 5.0V
- Specified from $-40^{\circ}C$ to $+125^{\circ}C$
- Packaging information: SOT23-5/SOT353

Ordering Information:

Reel packing specifications:

Part number	Packaging form	Marking code	Reel quantity	Boxed reel quantity	Notes
AiP74LV1T32GB235.TR	SOT23-5	GFXX	3000 PCS/reel	30000 PCS/box	Dimensions of plastic enclosure: 2.9mm×1.6mm Pin spacing: 0.95mm
AiP74LV1T32GC353.TR	SOT353	GFXX	3000 PCS/reel	30000 PCS/box	Dimensions of plastic enclosure: 2.1mm×1.3mm Pin spacing: 0.65mm

Note 1: "XX" refers to variable content, meaning year and package batch serial number.

Note 2: If the physical information is inconsistent with the ordering information, please refer to the actual product.



2、Block Diagram And Pin Description

2.1、Block Diagram




Figure 1. Logic symbol





Figure 2. Logic diagram

2.2、Pin Configurations



2.3、Pin Description

Pin No.	Pin Name	Description
1	B	data input
2	A	data input
3	GND	ground (0V)
4	Y	data output
5	V _{CC}	supply voltage



2.4、Function Table

Input		Output
A	B	Y
L	L	L
L	H	H
H	L	H
H	H	H

Note: H=HIGH voltage level; L=LOW voltage level.

3、Electrical Parameter

3.1、Absolute Maximum Ratings

(Voltage are referenced to GND (ground=0V), unless otherwise specified)

Characteristic	Symbol	Conditions	Min.	Max.	Unit
supply voltage	V_{CC}	-	-0.5	+7.0	V
input voltage	V_I	-	-0.5	+7.0	V
output voltage	V_O	output HIGH or LOW state	-0.5	$V_{CC}+0.5$	V
		output in power-off state	-0.5	+4.6	V
supply current	I_{CC}	-	-	50	mA
ground current	I_{GND}	-	-50	-	mA
input clamping current	I_{IK}	$V_I < 0V$	-20	-	mA
output current	I_O	$V_O = 0V$ to V_{CC}	-	± 25	mA
output clamping current	I_{OK}	$V_O < 0V$ or $V_O > V_{CC}$	-	± 20	mA
storage temperature	T_{stg}	-	-65	+150	°C
soldering temperature	T_L	10s	260		°C

3.2、Recommended Operating Conditions

(Voltages are referenced to GND (ground=0V), unless otherwise specified)

Parameter	Symbol	Conditions	Min.	Typ.	Max.	Unit
supply voltage	V_{CC}	-	1.6	5.0	5.5	V
input voltage	V_I	-	0	-	5.5	V
output voltage	V_O	output HIGH or LOW state	0	-	V_{CC}	V
ambient temperature	T_{amb}	-	-40	-	+125	°C
input transition rise and fall rate	$\Delta t / \Delta V$	$V_{CC} = 1.8V$ to $5.0V$	-	-	20	ns/V



3.3、Electrical Characteristics

3.3.1、DC Characteristics 1

($T_{amb}=25^{\circ}\text{C}$, voltages are referenced to GND (ground=0V), unless otherwise specified)

Parameter	Symbol	Conditions		Min.	Typ.	Max.	Unit
HIGH-level input voltage	V_{IH}	$V_{CC}=1.65V$ to $1.8V$		0.94	-	-	V
		$V_{CC}=2.0V$		0.99	-	-	V
		$V_{CC}=2.25V$ to $2.5V$		1.135	-	-	V
		$V_{CC}=2.75V$		1.21	-	-	V
		$V_{CC}=3.0V$ to $3.3V$		1.35	-	-	V
		$V_{CC}=3.6V$		1.47	-	-	V
		$V_{CC}=4.5V$ to $5.0V$		2.02	-	-	V
		$V_{CC}=5.5V$		2.10	-	-	V
LOW-level input voltage	V_{IL}	$V_{CC}=1.65V$ to $2.0V$		-	-	0.58	V
		$V_{CC}=2.25V$ to $2.75V$		-	-	0.75	V
		$V_{CC}=3.0V$ to $3.6V$		-	-	0.80	V
		$V_{CC}=4.5V$ to $5.5V$		-	-	0.80	V
HIGH-level output voltage	V_{OH}	$V_I=V_{IH}$ or V_{IL}	$V_{CC}=1.65V$ to $5.5V$; $I_O=-20\mu A$	$V_{CC}-0.1$	-	-	V
			$V_{CC}=1.65V$; $I_O=-2mA$	1.28	-	-	V
			$V_{CC}=1.8V$; $I_O=-2mA$	1.5	-	-	V
			$V_{CC}=2.3V$; $I_O=-2.3mA$	2.0	-	-	V
			$V_{CC}=2.3V$; $I_O=-3mA$	2.0	-	-	V
			$V_{CC}=2.5V$; $I_O=-3mA$	2.25	-	-	V
			$V_{CC}=3.0V$; $I_O=-3mA$	2.78	-	-	V
			$V_{CC}=3.0V$; $I_O=-5.5mA$	2.6	-	-	V
			$V_{CC}=3.3V$; $I_O=-5.5mA$	2.9	-	-	V
			$V_{CC}=4.5V$; $I_O=-4mA$	4.2	-	-	V
			$V_{CC}=4.5V$; $I_O=-8mA$	4.1	-	-	V
			$V_{CC}=5.0V$; $I_O=-8mA$	4.6	-	-	V
LOW-level output voltage	V_{OL}	$V_I=V_{IH}$ or V_{IL}	$V_{CC}=1.65V$ to $5.5V$; $I_O=20\mu A$	-	-	0.1	V
			$V_{CC}=1.65V$; $I_O=2mA$	-	-	0.2	V
			$V_{CC}=2.3V$; $I_O=2.3mA$	-	-	0.1	V
			$V_{CC}=2.3V$; $I_O=3mA$	-	-	0.15	V
			$V_{CC}=3.0V$; $I_O=3mA$	-	-	0.1	V
			$V_{CC}=3.0V$; $I_O=5.5mA$	-	-	0.2	V
			$V_{CC}=4.5V$; $I_O=4mA$	-	-	0.15	V
			$V_{CC}=4.5V$; $I_O=8mA$	-	-	0.3	V
input leakage current	I_I	$V_I=V_{CC}$ or GND; $V_{CC}=0V$ to $5.5V$		-	-	± 1	μA
supply current	I_{CC}	$V_I=V_{CC}$ or GND; $I_O=0A$; $V_{CC}=1.8V, 2.5V, 3.3V, 5.0V$		-	-	1	μA
additional supply current	ΔI_{CC}	per input pin; $V_{CC}=1.8V$; $V_I=0.3V$ or $1.1V$; $I_O=0A$; other pins at V_{CC} or GND		-	-	10	μA



		per input pin; $V_{CC}=5.5V$; $V_I=0.3V$ or $3.4V$; $I_O=0A$; other pins at V_{CC} or GND	-	-	1.35	mA
--	--	--	---	---	------	----

3.3.2、DC Characteristics 2

($T_{amb}=-40^{\circ}C$ to $+85^{\circ}C$, voltages are referenced to GND (ground=0V), unless otherwise specified)

Parameter	Symbol	Conditions	Min.	Typ.	Max.	Unit
HIGH-level input voltage	V_{IH}	$V_{CC}=1.65V$ to $1.8V$	1.0	-	-	V
		$V_{CC}=2.0V$	1.03	-	-	V
		$V_{CC}=2.25V$ to $2.5V$	1.18	-	-	V
		$V_{CC}=2.75V$	1.23	-	-	V
		$V_{CC}=3.0V$ to $3.3V$	1.37	-	-	V
		$V_{CC}=3.6V$	1.48	-	-	V
		$V_{CC}=4.5V$ to $5.0V$	2.03	-	-	V
		$V_{CC}=5.5V$	2.11	-	-	V
LOW-level input voltage	V_{IL}	$V_{CC}=1.65V$ to $2.0V$	-	-	0.55	V
		$V_{CC}=2.25V$ to $2.75V$	-	-	0.71	V
		$V_{CC}=3.0V$ to $3.6V$	-	-	0.65	V
		$V_{CC}=4.5V$ to $5.5V$	-	-	0.80	V
HIGH-level output voltage	V_{OH}	$V_I=V_{IH}$ or V_{IL} $V_{CC}=1.65V$ to $5.5V$; $I_O=-20\mu A$	$V_{CC}-0.1$	-	-	V
		$V_{CC}=1.65V$; $I_O=-2mA$	1.21	-	-	V
		$V_{CC}=1.8V$; $I_O=-2mA$	1.45	-	-	V
		$V_{CC}=2.3V$; $I_O=-2.3mA$	2.0	-	-	V
		$V_{CC}=2.3V$; $I_O=-3mA$	1.93	-	-	V
		$V_{CC}=2.5V$; $I_O=-3mA$	2.15	-	-	V
		$V_{CC}=3.0V$; $I_O=-3mA$	2.7	-	-	V
		$V_{CC}=3.0V$; $I_O=-5.5mA$	2.49	-	-	V
		$V_{CC}=3.3V$; $I_O=-5.5mA$	2.8	-	-	V
		$V_{CC}=4.5V$; $I_O=-4mA$	4.1	-	-	V
		$V_{CC}=4.5V$; $I_O=-8mA$	3.95	-	-	V
		$V_{CC}=5.0V$; $I_O=-8mA$	4.5	-	-	V
LOW-level output voltage	V_{OL}	$V_I=V_{IH}$ or V_{IL} $V_{CC}=1.65V$ to $5.5V$; $I_O=20\mu A$	-	-	0.1	V
		$V_{CC}=1.65V$; $I_O=2mA$	-	-	0.25	V
		$V_{CC}=2.3V$; $I_O=2.3mA$	-	-	0.15	V
		$V_{CC}=2.3V$; $I_O=3mA$	-	-	0.2	V
		$V_{CC}=3.0V$; $I_O=3mA$	-	-	0.15	V
		$V_{CC}=3.0V$; $I_O=5.5mA$	-	-	0.252	V
		$V_{CC}=4.5V$; $I_O=4mA$	-	-	0.2	V
		$V_{CC}=4.5V$; $I_O=8mA$	-	-	0.35	V
input leakage current	I_I	$V_I=V_{CC}$ or GND; $V_{CC}=0V$ to $5.5V$	-	-	± 1	μA
supply current	I_{CC}	$V_I=V_{CC}$ or GND; $I_O=0A$; $V_{CC}=1.8V, 2.5V, 3.3V, 5.0V$	-	-	10	μA



additional supply current	ΔI_{CC}	per input pin; $V_{CC}=1.8V$; $V_I=0.3V$ or $1.1V$; $I_O=0A$; other pins at V_{CC} or GND	-	-	10	μA
		per input pin; $V_{CC}=5.5V$; $V_I=0.3V$ or $3.4V$; $I_O=0A$; other pins at V_{CC} or GND	-	-	1.5	mA

3.3.3、DC Characteristics 3

($T_{amb}=-40^{\circ}C$ to $+125^{\circ}C$, voltages are referenced to GND (ground=0V), unless otherwise specified)

Parameter	Symbol	Conditions		Min.	Typ.	Max.	Unit
HIGH-level input voltage	V_{IH}	$V_{CC}=1.65V$ to $1.8V$		1.0	-	-	V
		$V_{CC}=2.0V$		1.03	-	-	V
		$V_{CC}=2.25V$ to $2.5V$		1.18	-	-	V
		$V_{CC}=2.75V$		1.23	-	-	V
		$V_{CC}=3.0V$ to $3.3V$		1.37	-	-	V
		$V_{CC}=3.6V$		1.48	-	-	V
		$V_{CC}=4.5V$ to $5.0V$		2.03	-	-	V
		$V_{CC}=5.5V$		2.11	-	-	V
LOW-level input voltage	V_{IL}	$V_{CC}=1.65V$ to $2.0V$		-	-	0.55	V
		$V_{CC}=2.25V$ to $2.75V$		-	-	0.71	V
		$V_{CC}=3.0V$ to $3.6V$		-	-	0.65	V
		$V_{CC}=4.5V$ to $5.5V$		-	-	0.80	V
HIGH-level output voltage	V_{OH}	$V_I=V_{IH}$ or V_{IL}	$V_{CC}=1.65V$ to $5.5V$; $I_O=-20\mu A$	$V_{CC}-0.1$	-	-	V
			$V_{CC}=1.65V$; $I_O=-2mA$	1.21	-	-	V
			$V_{CC}=1.8V$; $I_O=-2mA$	1.45	-	-	V
			$V_{CC}=2.3V$; $I_O=-2.3mA$	2.0	-	-	V
			$V_{CC}=2.3V$; $I_O=-3mA$	1.93	-	-	V
			$V_{CC}=2.5V$; $I_O=-3mA$	2.15	-	-	V
			$V_{CC}=3.0V$; $I_O=-3mA$	2.7	-	-	V
			$V_{CC}=3.0V$; $I_O=-5.5mA$	2.49	-	-	V
			$V_{CC}=3.3V$; $I_O=-5.5mA$	2.8	-	-	V
			$V_{CC}=4.5V$; $I_O=-4mA$	4.1	-	-	V
			$V_{CC}=4.5V$; $I_O=-8mA$	3.95	-	-	V
LOW-level output voltage	V_{OL}	$V_I=V_{IH}$ or V_{IL}	$V_{CC}=1.65V$ to $5.5V$; $I_O=20\mu A$	-	-	0.1	V
			$V_{CC}=1.65V$; $I_O=2mA$	-	-	0.25	V
			$V_{CC}=2.3V$; $I_O=2.3mA$	-	-	0.15	V
			$V_{CC}=2.3V$; $I_O=3mA$	-	-	0.2	V
			$V_{CC}=3.0V$; $I_O=3mA$	-	-	0.15	V
			$V_{CC}=3.0V$; $I_O=5.5mA$	-	-	0.252	V
			$V_{CC}=4.5V$; $I_O=4mA$	-	-	0.2	V
			$V_{CC}=4.5V$; $I_O=8mA$	-	-	0.35	V
input leakage current	I_I	$V_I=V_{CC}$ or GND; $V_{CC}=0V$ to $5.5V$		-	-	± 1	μA



supply current	I_{CC}	$V_I=V_{CC}$ or GND; $I_O=0A$; $V_{CC}=1.8V, 2.5V, 3.3V, 5.0V$	-	-	10	μA
additional supply current	ΔI_{CC}	per input pin; $V_{CC}=1.8V$; $V_I=0.3V$ or $1.1V$; $I_O=0A$; other pins at V_{CC} or GND	-	-	10	μA
		per input pin; $V_{CC}=5.5V$; $V_I=0.3V$ or $3.4V$; $I_O=0A$; other pins at V_{CC} or GND	-	-	1.5	mA

3.3.4、AC Characteristics 1

($T_{amb}=25^{\circ}C$, GND=0V, unless otherwise specified)

Parameter	Symbol	Conditions		Min.	Typ.	Max.	Unit
propagation delay	t_{pd}	A, B to Y; see Figure 4 ^[1]	$V_{CC}=1.8V$; $C_L=15pF$	-	6.6	9.6	ns
			$V_{CC}=1.8V$; $C_L=30pF$	-	7.7	10.8	ns
			$V_{CC}=2.5V$; $C_L=15pF$	-	4.7	6.6	ns
			$V_{CC}=2.5V$; $C_L=30pF$	-	5.4	7.4	ns
			$V_{CC}=3.3V$; $C_L=15pF$	-	3.9	5.3	ns
			$V_{CC}=3.3V$; $C_L=30pF$	-	4.4	6.0	ns
			$V_{CC}=5.0V$; $C_L=15pF$	-	3.2	4.0	ns
			$V_{CC}=5.0V$; $C_L=30pF$	-	3.7	4.5	ns

Note:

[1] t_{pd} is the same as t_{PLH} and t_{PHL} .

3.3.5、AC Characteristics 2

($T_{amb}=-40^{\circ}C$ to $+85^{\circ}C$, GND=0V, unless otherwise specified)

Parameter	Symbol	Conditions		Min.	Typ.	Max.	Unit
propagation delay	t_{pd}	A, B to Y; see Figure 4 ^[1]	$V_{CC}=1.8V$; $C_L=15pF$	-	-	10.9	ns
			$V_{CC}=1.8V$; $C_L=30pF$	-	-	12.3	ns
			$V_{CC}=2.5V$; $C_L=15pF$	-	-	7.5	ns
			$V_{CC}=2.5V$; $C_L=30pF$	-	-	8.4	ns
			$V_{CC}=3.3V$; $C_L=15pF$	-	-	6.0	ns
			$V_{CC}=3.3V$; $C_L=30pF$	-	-	6.8	ns
			$V_{CC}=5.0V$; $C_L=15pF$	-	-	4.5	ns
			$V_{CC}=5.0V$; $C_L=30pF$	-	-	5.1	ns

Note:

[1] t_{pd} is the same as t_{PLH} and t_{PHL} .



3.3.6、AC Characteristics 3

($T_{amb} = -40^{\circ}\text{C}$ to $+125^{\circ}\text{C}$, GND=0V, unless otherwise specified)

Parameter	Symbol	Conditions		Min.	Typ.	Max.	Unit
propagation delay	t _{pd}	A, B to Y; see Figure 4 ^[1]	V _{CC} =1.8V; C _L =15pF	-	-	11.7	ns
			V _{CC} =1.8V; C _L =30pF	-	-	13.3	ns
			V _{CC} =2.5V; C _L =15pF	-	-	8.0	ns
			V _{CC} =2.5V; C _L =30pF	-	-	9.1	ns
			V _{CC} =3.3V; C _L =15pF	-	-	6.4	ns
			V _{CC} =3.3V; C _L =30pF	-	-	7.3	ns
			V _{CC} =5.0V; C _L =15pF	-	-	4.7	ns
			V _{CC} =5.0V; C _L =30pF	-	-	5.4	ns

Note:

[1] t_{pd} is the same as t_{PLH} and t_{PHL} .

4、Testing Circuit

4.1、AC Testing Circuit




Figure 3. Test circuit for measuring switching time

Definitions test circuit:

C_L =Load capacitance including jig and probe capacitance

R_L =Load resistance



4.2、Test Data

Supply voltage	Input		Load		V _{EXT}		
V _{CC}	V _I	$\Delta t/\Delta V^{[1]}$	C _L	R _L	t _{PLH} , t _{PHL}	t _{PZH} , t _{PHZ}	t _{PZL} , t _{PLZ}
1.8V	V _{CC}	$\leq 1.0\text{ns/V}$	15pF, 30pF	1K Ω	Open	GND	V _{CC}
2.5V	V _{CC}	$\leq 1.0\text{ns/V}$	15pF, 30pF	1K Ω	Open	GND	V _{CC}
3.3V	3V	$\leq 1.0\text{ns/V}$	15pF, 30pF	1K Ω	Open	GND	V _{CC}
5.0V	3V	$\leq 1.0\text{ns/V}$	15pF, 30pF	1K Ω	Open	GND	V _{CC}

[1] $dV/dt \geq 1.0 \text{ V/ns}$

4.3、AC Testing Waveforms




Figure 4. The input A to output Y propagation delays



4.4、Measurement Points

Input	Output
V _M	V _M
0.5V _I	0.5V _{CC}



5、Package Information




5.1、SOT23-5



2023/12/A	Dimensions In Millimeters	
Symbol	Min.	Max.
A	—	1.26
A1	0.00	0.12
A2	1.00	1.20
b	0.30	0.50
c	0.10	0.20
D	2.82	3.02
E	2.60	3.00
E1	1.50	1.70
e	0.95	
e1	1.80	2.00
L	0.30	0.60
θ	0°	8°



5.2、SOT353



2023/12/A	Dimensions In Millimeters	
Symbol	Min.	Max.
A	0.90	1.10
A1	0.00	0.10
A2	0.90	1.00
b	0.15	0.35
c	0.11	0.175
D	2.00	2.20
E	1.15	1.35
E1	2.15	2.45
e	0.65	
e1	1.20	1.40
L	0.525	
L1	0.26	0.46
θ	0°	8°



6、Statements And Notes

6.1、The name and content of Hazardous substances or Elements in the product

Part name	Hazardous substances or Elements									
	Lead and lead compounds	Mercury and mercury compounds	Cadmium and cadmium compounds	Hexavalent chromium compounds	Polybrominated biphenyls	Polybrominated biphenyl ethers	Dibutyl phthalate	Butylbenzyl phthalate	Di-2-ethylhexyl phthalate	Diisobutyl phthalate
Lead frame	○	○	○	○	○	○	○	○	○	○
Plastic resin	○	○	○	○	○	○	○	○	○	○
Chip	○	○	○	○	○	○	○	○	○	○
The lead	○	○	○	○	○	○	○	○	○	○
Plastic sheet installed	○	○	○	○	○	○	○	○	○	○
explanation	○: Indicates that the content of hazardous substances or elements in the detection limit of the following the SJ/T11363-2006 standard. ×: Indicates that the content of hazardous substances or elements exceeding the SJ/T11363-2006 Standard limit requirements.									

6.2、Notes

We recommend you to read this chapter carefully before using this product.

The information in this chapter is provided for reference only and i-Core disclaims any express or implied warranties, including but not limited to applicability, special application or non-infringement of third party rights.

This product is not suitable for critical equipment such as life-saving, life-sustaining or safety equipment. It is also not suitable for applications that may result in personal injury, death, or serious property or environmental damage due to product malfunction or failure. I-Core will not be liable for any damages incurred by the customers at their own risk for such applications.

The customer is responsible for conducting all necessary tests i-Core's application to avoid failure in the application or the application of the customer's third party users. I-Core does not accept any liability.

The Company reserves the right to change or improve the information published in this chapter at any time. The information in this chapter are subject to change without notice. We recommend the customer to consult our sales staff before purchasing.

Please obtain related materials from i-Core's regular channels and we are not responsible for its content if it is provided by sources other than our company.

In case of any conflict between the Chinese and English version, the version is subject to the Chinese one.